

Technical Specifications

Display	Size	80-inch-class (80-inch [203.2 cm] diagonal) UV2 A*1 LCD
	Max. Resolution	1,920 x 1,080 pixels
	Installation	Landscape
	Brightness*2	350 cd/m2
	Pixel Pitch (H x V)	0.923 x 0.923 mm
	Contrast Ratio	5,000 : 1
	Viewing Angle (H/V)	1176°/176° (CR 10)
	Backlight	LED, direct lit
	Response Time	4 ms (grey to grey, avg.)
	Active Screen Area	1,771.2 x 996.3 mm (69 3 /4" x 39 1 /4")
Connectivity	Input Terminals*5	PC analogue: Mini D-sub 15-pin x 1, HDMITM x 3 (HDCP and 1080p compatible, PC / AV signal compatible), 3.5 mm-diameter mini stereo jack x 1, audio: RCA pin (L/R) x 1, video: RCA pin x 1*8 , component video: RCA pin x 1*8 , RS-232C D-sub 9-pin x 1
	Output Terminals*5	3.5 mm-diameter mini stereo jack x 1
Touchscreen	Touch Technology	IR (infrared blocking detection method)
	Touch Points	10 points
	Protection Glass	Thickness: Approx. 3.1 mm Shock resistance: 130 cm
General	Speaker Output	10 W + 10 W
Power	Power Supply	100V – 240V AC, 50/60 Hz
	Power Consumption	270 W
Operation Condition	Operating Temperature	5°C to 35°C
	Operating Humidity	20% to 80% RH (no condensation)
Dimension (W x D x H) (approx.) (Display only)		1,882 x 127 x 1,139 mm (74 1 /8" x 5" x 44 13/16")
Weight (approx.)		79 kg (174.2 lbs)